


new product range

Neatflex - the 3/4" range of bending substrates



Build custom curves with the performance characteristics you need for your project

- Moisture Resistant
- Lightweight
- Impact resistant
- Fire retardant
- FSC Certified

Go Red with Neatflex PIP fire retardant†

Class A material, Neatflex FR faced with Greenguard certified Polybak is ideal for applications in public buildings such as schools, hospitals, casinos and theatres where risk-assessment or specification determines that fire retardant materials should be used.

NEATFLEX
fire retardant

Go Green with Neatflex pip

Made from MOISTURE RESISTANT MDF faced with Greenguard certified PolyBak. The cost effective way to create one-piece 3/4" custom curves with the added benefit of moisture resistance.

NEATFLEX
bendy™ pip


Go Lite with Neatflex bendy ply

45% less weight than regular MDF with all the benefits of Plywood. Neatflex Ply is the original 3/4" product in the Neatflex family used widely in North America.

NEATFLEX
bendy™ ply

3/4" Product Summary - Neatflex


Product	Board size	Wrap	Performance characteristic	Nominal Thickness	Weight
Neatflex Ply	96" x 48"	Barrel	Lightweight	3/4"	51 lbs
Neatflex PIP*	96" x 48"	Barrel	Moisture Resistant	3/4"	72 lbs
Neatflex PIP*	48" x 96"	Column	Moisture Resistant	3/4"	72 lbs
Neatflex PIP FR*	96" x 48"	Barrel	*Fire Retardant – Class A	3/4"	72 lbs



† Visit www.neatconcepts.com/fire for a copy of the Southwest Research Institute fire test report on Neatflex FR.

sensational

Neatform - the 1/4" and 3/8" range of bending substrates



Made exclusively from 1/4" and 3/8" thick, 80% FSC Certified MDF, Neatform is perfect for creating custom curves.

Now available with
No Added Formaldehyde (NAF),
CARB Phase 1 compliant

Neatform curves are whatever you want them to be

framed and frameless, lightweight, tough, smooth, paintable, laminated, veneered

Material Benefits

- Ready to paint and stain
- Consistent thickness and bending capability
- Excellent seam hiding qualities
- Follows intended curves without bumps and hollows
- Repeatability is great and results are predictable


NEATFORM
bendy™ mdf

1/4" & 3/8" Product Summary - Neatform Bendy MDF

Board size	Wrap	Face	Nominal Thickness	Weight
96" x 48"	Barrel	Sanded - 120 grit	1/4"	23.4 lbs
48" x 96"	Column	Sanded - 120 grit	1/4"	23.4 lbs
96" x 48"	Barrel	Sanded - 120 grit	3/8"	33.4 lbs
48" x 96"	Column	Sanded - 120 grit	3/8"	33.4 lbs



48" x 96"
Long-Cut
Column Wrap



96" x 48"
Cross-Cut
Barrel Wrap

Neatform and Neatflex Radius Chart

Product	Nominal Thickness	Minimum Radius*	Minimum Diameter*
Neatform	1/4"	4" to 6"	8" to 12"
Neatform	3/8"	6" to 8"	12" to 16"
Neatflex	3/4"	10" to 12"	20" to 24"

* Minimum radii and diameters vary with temperature, humidity and any surface materials such as veneer or laminate applied to the surface before bending.

All Neatform and Neatflex products are made from a combination of 80% FSC Certified MDF, plywood and PolyBak, which is Greenguard certified in the USA.



Neat Concepts FSC
Chain of Custody
No. TT-COC-1958

Distributor

Email: northamerica@neatconcepts.com
Web site: www.neatconcepts.com

